

CP-NVR-8CH



P2P Mobile App:

VSSMOBILE



CPCAM 8CH POE UHD 5MP NVR

FEATURES

- Up to 5 Mega pixels IP camera recording
- Input 8ch D1, 720P or 1080P real time recording;
- Max 8ch playback synchronously
- 8 POE ports support standard 802.3af
- On-board 2 SATA port, each one supports 6 TB
- Smart face detection and Perimeter detection
- Alarm and talk-back supported
- ONVIF 2.2 supported and compatible with almost all third-party IP cameras
- 3D intelligent PTZ control via USB Mouse
- VGA, HDMI[®] and CVBS output sync
- HDMI[®] and VGA resolution up to 1920×1080P
- Built-in P2P Cloud service, firewall penetration automatically
- Always online , no need configuration for remote view anymore
- Mass of network protocols NTP, Email, RTSP, UPNP
- Support iPhone, Android APP
- Internet Explorer, Firefox and center monitoring client supported

➤ SPECIFICATIONS

▼ Input

IP Camera Input	8 channel
Handling Capacity	80Mbps
Recommend Input	8*D1@30fps(2Mbps) 8*720P@30fps(4Mbps) 8*1080P@30fps(8Mbps)
Audio In	G711A@64Kbps(need IP camera support)
Talk-back	1 Line-in

▼ Output

Interface	1 HDMI, 1 VGA, 1 BNC
Resolution	1920×1080, 1280×1024, 1280×720, 1024×768,800×600
Screen Split	1/4/8/9
Audio Out	1 BNC, 2.0 Vp-p,300 ohms

▼ Record

Compression	H.264 / MPEG-4
Resolution	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Bit Rate	64~ 8192kbps
Record Mode	Manual, Schedule, MD, Alarm, Stop

▼ Alarm

Smart Detection	<input type="checkbox"/> 1-ch face detection or Perimeter detection
Trigger Event	Alarm, Recording, PTZ movement, Video Push out, Capture, Send Email, FTP, Buzzer , etc.
Video Detection	Motion Detection, MD Zones: grid 22×18, Video Loss
Alarm Pre-record	1~30 seconds adjustable
Alarm Input	8 channel
Alarm Output	1 channel, switch

▼ Playback & Backup

Sync Playback	1/4/8
Playback Function	Timeline Play, Pause, Stop, Rewind, Fast play, Slow play, Step, Full screen, Digital zoom
Backup Mode	USB / Network

▼ Network

Networking Style	Ethernet(RJ-45 10/100Mbps), 3G dongle
Network Function	P2P, UPNP, RTSP, UDP, SMTP, NTP, DHCP, IP Filter, PPPOE, DDNS, FTP, Alarm Server, etc.
Smart devices	iPhone, iPad, Android, Windows Phone, support QR Code login

▼ Storage

HDD Slot	2 SATA ports, SMART
USB	2 * USB2.0 (Front for reuse)

▼ Others

Power Supply	DC12V/3.3A & DC 48V/1.875A
POE	8 RJ-45, 802.3af
Dimension (mm)	360x48x260
Power Consumption	<10W (without HDD & POE)
Working Environment	-10°C ~+55°C / 10%~90%RH

REAR PANEL

